

Glass



This series is made up of a series of cabinets manufactured in hot pressed polyester reinforced with fibre glass, halogen free, which gives the series a really high performance level.

There are IP66 cabinets, and are available in 7 different sizes, in RAL9002 grey colour. They are symmetric and reversible in many cases, thus obtaining a high degree of versatility for carrying all types of electric, pneumatic, hydraulic and communications installations, etc. The base is manufactured in just one piece thus guaranteeing optimum inner space and increasing its resistance to impact.

There are also cabinets which have an IP55 degree of protection (1000 (H) x 750 (W)), made in RAL7035 grey colour.

Its double insulation characteristics guarantee maximum safety both for the installations and for persons.

■ POLYESTER ENCLOSURES IP66-IP55



TECHNICAL DATA IP66

■ degree of protection	IP66
■ resistance to impact:	
opaque door:	IK10
transparent door:	IK08
■ range of temperature under normal conditions:	
	-50°C/+90°C
■ test of resistance to glow wire	960°C
■ thermic class	150°C
■ materials	Hot moulded fibreglass reinforced polyester (GRP)
■ colour	RAL 9002

According to low tension directive 2006/95/CE
Norms: UNE-EN 62208 and UNE-EN 61439-1-3 (in the affected parts)

TECHNICAL DATA IP55

■ degree of protection	IP55
■ resistance to impact	IK10
■ range of temperature under normal conditions:	
	-50°C/+90°C
■ test of resistance to glow wire	960°C
■ thermic class	150°C
■ materials	Hot moulded fibreglass reinforced polyester (GRP)
■ colour	RAL 7035

According to low tension directive 2006/95/CE
Norms: UNE-EN 62208 and UNE-EN 61439-1-3 (in the affected parts)

Glass

■ POLYESTER ENCLOSURES IP66-IP55

■ OPAQUE DOOR CABINETS



Model	Dimension (HxWxD)	STK1
POL302514	300X250X140	4,401
POL403020	400X300X200	5,682
POL404020	400X400X200	6,593
POL504020	500X400X200	8,020
POL604023	600X400X230	9,238
POL605023	600X500X230	10,391
POL806030	800X600X300	16,593

■ TRANSPARENT DOOR CABINETS



Model	Dimension (HxWxD)	STK1
POL302514PT	300X250X140	6,519
POL403020PT	400X300X200	8,732
POL404020PT	400X400X200	10,786
POL504020PT	500X400X200	12,866
POL604023PT	600X400X230	14,833
POL605023PT	600X500X230	18,023
POL806030PT	800X600X300	27,261

Supplied without the necessary accessories for direct wall mounting



TECHNICAL DATA IP66

■ degree of protection	IP66
■ resistance to impact:	
opaque door:	IK10
transparent door:	IK08
■ range of temperature under normal conditions:	-50°C/+90°C
■ test of resistance to glow wire	960°C
■ thermic class	150°C
■ materials	Hot moulded fibreglass reinforced polyester (GRP)
■ colour	RAL 9002

According to low tension directive 2006/95/CE
Norms: UNE-EN 62208 and UNE-EN 61439-1-3 (in the affected parts)

GLASS IP66 accessories

POLYESTER BASE PLATE



Model	Dimension (HxWxD)	STK1
PPL3025	300X250	308
PPL4030	400X300	429
PPL4040	400X400	586
PPL5040	500X400	769
PPL6040	600X400	1,019
PPL6050	600X500	1,200
PPL8060	800X600	2,170

METAL BASE PLATE



Model	Dimension (HxWxD)	STK1
PML3025	300X250	284
PML4030	400X300	424
PML4040	400X400	526
PML5040	500X400	631
PML6040	600X400	769
PML6050	600X500	959
PML7550	750X500	N/A
PML8060	800X600	1,485

BAQUELITE BASE PLATE



Model	Dimension (HxWxD)	STK1
PBL3025	300X250	1,280
PBL4030	400X300	1,508
PBL4040	400X400	1,706
PBL5040	500X400	1,918
PBL6040	600X400	2,718
PBL6050	600X500	3,049
PBL8060	800X600	3,980
PBL10075	1000X750	4,953

MODULAR CHASSIS



Model	Modules	Rows	Dimension (HxWxD)	STK1
PCH4030	24	2x12	400x300	4,732
PCH4040	36	2x18	400x400	5,128
PCH5040	54	3x18	500x400	6,167
PCH6040	54	3x18	600x400	6,640
PCH6050	69	3x23	600x500	6,784
PCH8060	116	4x29	800x600	9,262

GLASS IP66 accessories

INNER DOOR



Model	Dimension (HxWxD)	ŞİFİ
PPIN4030	400X300	3,626
PPIN4040	400X400	3,989
PPIN5040	500X400	4,552
PPIN6040	600X400	4,860
PPIN6050	600X500	4,631
PPIN8060	800X600	7,145

SURFACE MOUNTING



Model	Detail	ŞİFİ
29221	4 wall fixing set with head-insulated screws	228
29222	4 set of adjustables brackets	347

ADJUSTABLE BASE PLATE



Model	For Depth cabinets (mm)	ŞİFİ
29223	200	1,749
29224	230	1,749
29225	300	2,104

LOCKS



Model	Detail	ŞİFİ
29229	Standard double bit lock	532
29230	Triangular screw 11mm	215
29231	Manual with key lock	650
29266	Zinc blockage lock	327

GLASS IP55

■ SINGLE DOOR WALL MOUNTING POLYESTER ENCLOSURES



IP55

DEPTH 300

Model	Detail	₺
POL505030	510x500x312	20,654
POL755030	760x500x312	23,633
POL1005030	1010x500x312	27,781
POL1007530	1010x750x312	32,669
POL1255030	1260x500x312	33,502
POL1257530	1260x750x312	37,608

DEPTH 420

Model	Detail	₺
POL1007542	1010x750x432	35,435
POL1257542	1260x750x432	40,372

■ SINGLE DOOR WALL MOUNTING POLYESTER CABINET WITH BOTTOM OPEN



IP55

DEPTH 300

Model	Detail	₺
POL505030/A	510x500x312	20,813
POL755030/A	760x500x312	23,792
POL1005030/A	1010x500x312	27,940
POL1007530/A	1010x750x312	32,875
POL1255030/A	1260x500x312	33,661
POL1257530/A	1260x750x312	37,814

DEPTH 420

Model	Detail	₺
POL1007542/A	1010x750x432	35,675
POL1257542/A	1260x750x432	40,612

■ SINGLE DOOR WALL MOUNTING POLYESTER CABINET WITH OVERHANG CANOPY



IP55

DEPTH 300

Model	Detail	₺
POL505030/T	510x500x312	22,810
POL755030/T	760x500x312	25,789
POL1005030/T	1010x500x312	29,937
POL1007530/T	1010x750x312	35,156
POL1255030/T	1260x500x312	35,658
POL1257530/T	1260x750x312	40,095

DEPTH 420

Model	Detail	₺
POL1007542/T	1010x750x432	38,027
POL1257542/T	1260x750x432	42,964

GLASS IP55

■ BASE PLATE



■ FIXED BASE PLATE

Polyester

Model	Detail	S1R1
PPL5050	393x40	674
PPL7550	750x500	1,183
PPL10050	893x405	1,866
PPL10075	1000x750	3,418
PPL12550	1143x405	2,736
PPL12575	1250x750	4,376

Metal

Model	Detail	S1R1
PML5050	393x40	528
PML7550	750x500	1,153
PML10050	893x405	N/A
PML10075	1000x750	3,102
PML12550	1143x405	N/A
PML12575	1250x750	3,756

■ ADJUSTABLE PLATE PACK

Polyester

Model	Detail	S1R1
29235	Cabinet depth 300 mm	2,100
29236	Cabinet depth 420 mm	2,353

■ POLYESTER PEDESTAL



Painted in black

Model	Dimension (mm)	S1R1
ZOC5030/P	60X500X300	6,670
ZOC7530/P	60X750X300	8,427
ZOC7542/P	60X750X420	9,283

■ SURFACE BRACKETS



Model	Detail	S1R1
29240	Group of 4 brackets made of zinc steel	882

■ LOCKS WITH SWING HANDLE



Model	Detail	S1R1
29241	Standard double-bit lock	2,452
29242	Triangular screw 11mm	2,452
29243	Manual with key look	2,452